

High Performance 2INCH MOBILE PRINTER WSP-i250

The Most rugged and reliable performance for diverse industry field.
The advent of i-family portable printer leads to huge breakthrough in mobile communication.

Features

- Durable Rugged Design
- Water-resistant construction
- High speed (80mm/sec)
- Wireless LAN (802.11 b/g) interface [option]
- MSR : Support Triple tracks (1&2&3 tracks) [option]
- Support Graphic LCD(128×32dots) with Blue LED Backlight
- High performance : Print labels & Support back feeding
- One touch paper cover
- Printer door open & Paper-out sensor
- In field programming – Update Firmware, Download Fonts and Logos
- Compact and easy to carry around
- Flow control : Software (XON/XOFF)
- ※ Hardware flow control not supported in printer.



MSR (optional)



Belt clip



Applications

Field sales and service, Transportation, Hospitality, Parking, Utility billing, safety, Material management, Law enforcement

Receipt



Mobile
POS



Transportation



Banking



Delivery
Report



Parking



Warehouse



Specification

Item	Specification
	MSR & Smart card reader (option), IP54
Printing	Direct thermal line printing
Characters per line	42cpl (MAX)
Characters size	Eng : 9*24 dots, 12*24 dots Kor : 16*24 dots, [24*24 dots]
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.
Resolution	203 dpi, 8 dots/mm
Print width	2-inch (48mm, 384dots)
Printing speed	80 mm/sec (MAX)
Dimensions	92.12 x 140.56 x 59.75mm (Standard) 92.12 x 144.47 x 59.75mm (MSR option)
Interface	· UART(RS-232C or TTL) · Bluetooth Ver 2.1 + EDR · Wireless LAN (802.11b/g) [option], USB [option]
Paper supplied	Thermal roll paper (58mm wide, 50ø) , Paper thickness : 60±5 μ m
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix
Driver	Microsoft Windows XP / VISTA / 7 , Windows CE, Linux, Android OS driver compatible
H/W Spec.	MCU : 32 bits RISC, FLASH : 4 Mbytes, RAM : 8 Mbytes
Receive buffer size	1M bytes
Battery	Rechargeable 7.4V DC , 1400mAh / 1800mAh / 2200mAh (Li-ion)
Battery duration	1 hour continuous printing
Battery charger	Input (100~250VAC, 50~60Hz), Output(8.4VDC/0.8A), 4hours full charge time
MSR	Triple tracks (1&2&3 tracks) [Option]
Smart card reader	ISO 7816 Compliant (EMV level 1 Certified) / T=0, T=1 support / 2 SAM (Security Application Module) [Option]
LCD	128×32 Dots FSTN (Blue LED Backlight)

Accessories



Battery charger



Roll paper



Interface cable

<Option>



Car charger