

# General Purpose Corded Area Imager Bar Code Reader

The Gryphon™ 4000 series represents the premium level of data collection devices from Datalogic Scanning for general purpose applications. Designed with people in mind, the Gryphon™ I GD4400-B All-in-One imager blends advanced 2D decoding with motion sensing technology, producing a user-friendly device with outstanding performance.

Featuring Datalogic's Motionix™ motionsensing technology, the Gryphon I GD4400-B imager senses the actions of the operator to automatically switch the device into handheld or presentation mode scanning. When picked up or set down, Motionix technology transitions the device seamlessly, eliminating the need to scan a label or rely on a mechanical switch.

As an All-in-One device, the Gryphon I GD4400-B scanner's permanent tilting stand is joined with an ergonomic handheld reader for handheld and presentation reading. The All-in-One imager adjusts to any angle to fit individual scanning preferences. The cable connection

is positioned well above the counter to avoid damage caused by spills.

User comfort is maximized with the Gryphon I GD4400-B imager's steady, deep red illumination light. Easier on the eyes than competitive products with flicker illumination, the highly visible 4-Dot aimer defines a precise reading zone and reduces accidental reads. The aimer's center cross provides a locator for targeted scanning in a multiple bar code environment.

The Gryphon I GD4400-B imager provides snappy, omnidirectional reading performance on all common 1D and 2D codes as well as postal, stacked and composite codes like PDF417. For mobile marketing or ticketing applications, this scanner also offers excellent reading performance on bar codes from mobile devices.

With enhanced optics, the Gryphon I GD4400-B imager boasts improved motion tolerance and high speed imaging to read fast moving codes. This reader also eliminates the need for separate equipment for signature capture and document scanning applications.

#### **Features**

- Motionix™ motion-sensing technology for seamless reading mode transitions
- Highly visible 4-Dot aimer with center cross for targeted scanning
- Permanent tilting stand for handheld or presentation omnidirectional reading
- Tilt Angle: + 30° / 15°
- Advanced motion tolerance optics
- Image capture and document scanning capabilities
- Reads 1D, 2D and postal codes plus stacked and composite codes
- Multi-interface options: RS-232 / IBM 46XX / USB or RS-232 / USB / Keyboard Wedge / Wand
- Datalogic's patented 'Green Spot' for good-read feedback











www.scanning.datalogic.com



# Specifications

### **DECODING CAPABILITY**

1D / LINEAR CODES

2D CODES

**POSTAL CODES** 

STACKED CODES

**ELECTRICAL** 

**CURRENT** 

STANDBY/IDLE (TYPICAL) INPUT VOLTAGE

**ENVIRONMENTAL** 

**AMRIENT LIGHT** DROP RESISTANCE ESD PROTECTION (AIR DISCHARGE) HUMIDITY (NON-CONDENSING)

PARTICULATE AND WATER SEALING **TEMPERATURE** 

**INTERFACES** 

PHYSICAL CHARACTERISTICS

**COLORS AVAILABLE** DIMENSIONS WEIGHT

**READING PERFORMANCE** 

**IMAGE CAPTURE IMAGER SENSOR** LIGHT SOURCE MOTION TOLERANCE

PRINT CONTRAST RATIO (MINIMUM)

**READING ANGLE** 

**READING INDICATORS** 

**RESOLUTION (MAXIMUM)** 

READING RANGES

TYPICAL DEPTH OF FIELD

**SAFETY & REGULATORY** 

AGENCY APPROVALS

ENVIRONMENTAL COMPLIANCE LASER CLASSIFICATION

**UTILITIES** 

DATALOGIC ALADDIN™

OPOS / JAVAPOS

REMOTE HOST DOWNLOAD

WARRANTY

5-Year Factory Warranty

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear

Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code;

QR Code

Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)

EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional;

MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

Operating (Typical): GD4410-B: < 170 mA @ 5 VDC GD4430-B: < 160 mA @ 5 VDC

65 mA @ 5 VDC

GD4410-B: 4.0 - 14.0 VDC; GD4430-B: 4.2 - 5.25 VDC

0 - 100.000 lux

Withstands repeated drops from 1.5 m / 5.0 ft onto a concrete surface

16 kV 5 - 95% IP52

Operating: 0 to 50 °C / 32 to 122 °F

Storage/Transport: -20 to 70 °C / -4 to 158 °F

GD4410-B: RS-232 / IBM 46XX / USB Multi-Interface

GD4430-B: RS-232 / USB / Keyboard Wedge / Wand Multi-Interface

Black; White 19.2 x 8.9 x 11.9 cm / 7.5 x 3.5 x 4.7 in

368.5 g / 13.0 oz

Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2

Wide VGA: 752 x 480 pixels Aiming: 650 nm VLD

Pitch: +/- 40°; Roll (Tilt): 180°; Skew (Yaw): +/- 40°

Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback;

Good Read LED

1D Linear: 0.102 mm / 4.0 mils; Data Matrix: 0.178 mm / 7.0 mils;

PDF417: 0.127 mm / 5.0 mils

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

Standard Range (SR)

Code 39: 5 mils: 4.0 to 19.0 cm / 1.6 to 7.5 in Code 39: 10 mils: 1.0 to 30.0 cm / 0.4 to 11.8 in Data Matrix: 10 mils: 2.0 to 16.0 cm / 0.8 to 6.3 in Data Matrix: 15 mils: 0 to 23.6 cm /0 to 9.3 in EAN-13: 13 mils: 1.5 to 40.0 cm / 0.6 to 15.7 in PDF417: 10 mils: 0.5 to 22.0 cm / 0.2 to 8.6 in QR Code: 10 mils: 3.0 to 12.5 cm / 1.2 to 4.9 in

The product meets necessary safety and regulatory approvals for its intended use.

The Quick Reference Guide for this product can be referred to for a complete list of certifications.

Complies to China RoHS: Complies to EU RoHS

Caution Laser Radiation - Do not stare into beam; IEC 60825 Class 2

Datalogic Aladdin configuration program is available for download at no charge.

JavaPOS Utilities are available for download at no charge.

OPOS Utilities are available for download at no charge. Lowers service costs and improves operations.



- Replace of the latest and international laws.
- Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic and the Datalogic Roya are Tegisters trademarks of Datalogic S.p.A. in many countries including the U.S.A. and the E.U. Datalogic Aladdin is a trademark of Datalogic Scanning Group S.r.I.

Other brand and product names may be trademarks of their respective owners.

www.scanning.datalogic.com



Phone: 1-800-351-9962 Fax: 1-312-212-1800

# About BarcodesInc

#### Who We Are

BarcodesInc is North America's leading provider of •] ^&  $\hat{a}$   $\hat{a}$ 

### We Owe Our Success To You

# Why Choose BarcodesInc?

## Dedicated Account A UbU[ Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

### **Highly-Trained Technical Support**

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

### Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

### Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same & È

### **Premier Access to Top Manufacturers**

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

### **Responsive Customer Service**

Every phone call and email is responded to promptly, completely and accurately by our customer service & æ È

## **Easy Returns**

Damaged, defective or incorrectly ordered goods may be returned without hassle.

### **BRANDS**





Intermec

Honeywell

ODATALOGIC.











unitech





Microsoft\*



symbol\*

AND MORE