

SPP-R200III

2인치 모바일 프린터



모바일 POS



우편·택배




고객서비스



티케팅

A True Companion for Mobile Solutions



Compatible with



Made for iPod iPhone iPad



프리미엄 모바일 솔루션의 아이콘

- 다양한 유무선 통신 지원 (블루투스, 와이파이, USB, 시리얼)
- NFC 태그 탑재로 자동 블루투스 페어링 지원
- 안드로이드, iOS, 윈도우 등 모바일 운영체제와 호환
- 애플 MFi 인증 모델 옵션 (iOS 모드-표준 블루투스 모드 자동 전환 기능)
- 마그네틱 카드 리더 (MSR) 옵션



2.1m



1.5m MSR



현장 업무에 최적화된 러기드 디자인

- 작고 견고한 본체와 228g의 가벼운 무게
- 2.1m (1.5m - MSR 모델) 낙하충격시험 통과
- IP43 (printer only) / IP54 (with protective case) 방수 방진 기능
- 다양한 휴대용, 충전용 액세서리 지원
- 배터리 완충 후 연속 출력 - 40mm 용지 기준 10롤 (총 145m)
- 배터리 완충 후 대기시간 - 24시간 (블루투스 모델 슬립모드 기준)



100 mm/sec

세계 시장을 선도하는 프린팅 기술

- 기존 모델 대비 10% 이상 빨라진 영수증 인쇄 속도 (100 mm/sec)
- 피드 버튼으로 영수증-라벨 인쇄 모드 전환 기능 지원
- 스티키 라벨 인쇄 옵션
- 58mm 혹은 50mm (옵션) 의 최대 인쇄 영역 너비

Made for iPod iPhone iPad

SPP-R200III

2인치 모바일 프린터



The World's No.1
Mobile Receipt Printer Manufacturer



Reported by Chunchisha

Specifications

Printer Specifications

Print Method

Direct Thermal

Print Speed

Up to 100 mm/sec (Receipt)
Up to 80 mm/sec (Linerless)
12.5% pattern

Print Resolution

203 dpi

Print Width

Up to 48 mm

Sensor

Paper End: Reflective sensor
Paper Cover Open: Mechanical switch

Media Characteristics

Media Type

Receipt and Label, Linerless (Optional)

Media Width

58 mm
50 mm (Optional)

Media Roll Diameter

Up to 40 mm

Media Thickness

0.07 ± 0.005 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)

79.5 x 126.7 x 43.6 mm
(3.13 x 4.99 x 1.72 inch)

Weight

Including battery: 228 g (0.50 lbs.)
Including MSR: 238 g (0.52 lbs.)
Paper : 57 g (0.13 lbs.)

Battery

7.4 V Li-ion, 1,200 mAh, Rechargeable
Charging time: Up to 2.5 hrs

Performance Characteristics

Memory

64 Mbit SDRAM, 32 Mbit FlashROM

Interface Options

USB V2.0 FS
Serial
Bluetooth V3.0 + EDR
WLAN 802.11b/g/n
(Infrastructure, Ad-hoc, Wi-Fi Direct)
- WEP40/104, WPA1/2(PSK, EAP)

Environment Characteristics

Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity

Operating: 10 ~ 80% RH

Sealing

IP43 (IP54 with protective case)

Drop Rate

2.1 m (7 ft.) / 1.5 m (5 ft.) for MSR model

Software

Emulation

BXL / POS

Driver

Windows Driver, OPOS Driver, JPOS Driver,
Linux CUPS Driver

SDK

iOS SDK, Android SDK, Windows SDK

Fonts / Graphics / Symbologies

Character Size

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24
KOR, CHN, JPN: 24 x 24

Characters Per Line

Font A: 32 Font B, C: 42
KOR, CHN, JPN: 16

Character Sets

Alphanumeric: 95
Expanded Graphics: 128 x 33 page
International: 32

Graphics

Supporting user-defined fonts, graphics,
formats, layouts, and logos

Barcode Symbologies

1D: Codabar, Code 39, Code 93, Code 128,
EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D: Aztec, Data Matrix, GS1 Databar, MaxiCode,
PDF417, QR code

Accessories

Standard

Belt Clip, Battery Pack, Battery Charger,
Power Cord, Paper

Optional

Belt Strap, Case, Protective Case, Shoulder
Strap, Battery Pack_V2 (with outer contacts),
Single Battery Cradle, Single Docking Cradle,
Quad Battery Charger, Quad Docking Cradle,
Cigarette Lighter Charger, Vehicle Holder,
Serial/USB Cable, Cleaning Pen

Integrated Card Reader (Optional)

MSR

3 Track (T-DES/DUKPT(Optional))



BR-SPP-R200III-KR-JAN16-V1-NF

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co., Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.Bixolon.com

