IT4200General Purpose 2D Area Imager





Ergonomic Design - Linear imager performance, with the versatility of area imaging all in a small, sleek housing.

Omni-directional reading of 1D, PDF417, MicroPDF417, Postal, Matrix, and EAN•UCC Composite codes, and OCR fonts for the easiest ever data collection.

Image Capture - Class-leading image quality and image transfer speed provide crisp images in less than one second.

Connectivity – The most popular interfaces in one model. Uses the standard Hand Held Products cable set.

Intelligent Aiming Options - Distinctive green aimer provides superior illumination contrast and makes image capture applications fast and intuitive.



The IT4200 area imager from Hand Held Products combines the versatility of area imaging with the speed and cost of linear scanning for retail and commercial applications. Powered by Adaptus™ Imaging Technology, the IT4200 is full featured, fast, and cost effective.

Current and future manufacturing, retail, and commercial applications will involve much more than linear bar codes. EAN-UCC composite codes are beginning to appear in food stores, PDF codes are used for age verification in restricted item sales, and postal bar codes are used to sort mail. The omnidirectional reading capability of the IT4200 allows fast and easy reading of all these codes. Simply point and shoot. There's no need to align a scan line, or wait for a raster beam to open up.

Whether capturing a signature as proof of delivery, taking a picture for identification, or electronic data storage, image capture is an important part of current and future solutions. The Adaptus Imaging Technology powered IT4200 is equipped with Hand Held Products fifth generation imaging for best-in-class image quality and image transfer speed, all at very economical prices. Image capture has become a mainstream application requirement. Trust Hand Held Products to provide the industry's best imaging.

With no moving parts, the IT4200 is as durable as it is versatile. Hand Held Products has a reputation for products that are tough as nails. The IT4200 is no exception, and will provide years of service at a low cost.

To learn how the IT4200 can work for you, contact us at any of the locations listed on the back or visit us at www.handheld.com.

IT4200 Specifications

Performance

Aiming:

Green Aiming LED: 526nm +30nm

Image: 752x480. Binary, TIFF, or JPEG output.

7.5 mil Linear

Working Range:

IT4200 SF

IT4200 HD

IT4200 SR 8.3 mil Linear 13 mil UPC 6.6 mil PDF417 10 mil PDF417 15 mil Data Matrix 35 mil MaxiCode (.033cm) (.017cm) (.025cm) (.038cm) (.089cm) (.021cm) 3.5 in. (8.9cm) 2.1 in. (5.3cm) 4.4 in. (11.2cm) 3.1 in. (7.9cm) 2.3 in. (5.8cm) 2.0 in. (5.1cm) Near 7.5 in. (19.1cm) Far 13.1 in. (33.3cm) 6.1 in. (15.5cm) 8.9 in. (22.6cm) 10.1 in. (25.7cm) 12.9 in. (32.8cm)

6.6 mil PDF417

6.6 mil PDF417

10 mil PDF417

35 mil MaxiCode

15 mil Data Matrix

8.3 mil Data Matrix

15 mil QR Code

10 mil QR Code

(.019cm) (.033cm) (.017cm) (.025cm) (.038cm) (.038cm) Near 2.5 in. (6.4cm) 2.0 in. (5.1cm) 2.8 in. (7.1cm) 2.2 in. (5.6cm) 1.8 in. (4.6cm) 2.2 in. (5.6 cm) 6.4 in. (16.3cm) 8.8 in. (22.4cm) 5.9 in. (15.0cm) 7.5 in. (19.1cm) 7.4 in. (18.8cm) 7.1 in. (18.0cm) Far

13 mil UPC

13 mil UPC

(.033cm) (.017cm) (.021cm) (.025cm) (.069cm) Near 2.1 in. (5.3cm) 2.1 in. (5.3cm) 2.0 in. (5.1cm) 2.6 in. (6.6cm) 2.2 in. (5.6cm) Far 6.6 in. (16.8cm) 4.9 in. (12.4cm) 7.8 in. (19.8cm) 4.6 in. (11.7cm) 5.2 in. (13.2cm)

Skew Angle: ±40° <u>+</u>40° Pitch Angle:

Horizontal Velocity: 4 in. (10 cm) per second

Mechanical/Electrical

Dimensions

Length: 5.5 in. (14.0 cm) Height 5.3 in. (13.5 cm) Width: 2.6 in. (6.6 cm) Weight: 4.5 oz. (127.6 g) Housing: UL 94V0 grade **Power Requirements:** 5Vdc ±10% at scanner **Current Draw (Typical)** Input Scanning Idle 382 mA 53 mA

Power Supply

Noise Rejection: Maximum 100mV peak to peak, 10 to 100 kHz

Environmental

Temperature

Operating: +32°F to +122°F (0°C to +50°C) Storage: -40°F to 140°F (-40°C to +60°C) **Humidity:** 0 to 95%, non-condensing

Mechanical Shock: Operational after 25 drops from 4.9 ft. (1.5 m) to concrete

Ambient Light: Up to 100,000 lux (full sunlight) **ESD Protection:** Functional after 100 8kV discharges Vibration: Withstands 1G peak from 8 to 80 Hz

Agency: FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, C-Tick N10410

MTBF: per MIL-HDBK-217F Ground Benign exceeds 70,000 hours

Symbologies

Postal:

2 Dimensional: PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Code 49, and EAN•UCC Composite Linear: Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128, UPC, EAN, RSS, Codablock, and BC412*

*available to licensed users Postnet, Planet Code, British Post, Canadian Post, Japanese Post, KIX (Netherlands Post)

OCR Fonts: OCR-A. OCR-B

Interfaces: All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, USB, TTL level RS-232, wand emulation

mode, TTL level Serial Wedge.

Warranty: Two year factory warranty.

Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY Tel: +1 315 685 8945 or, in North America: +1 800 582 4263 napresales@handheld.com Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@ handheld.com

Offices Serving Europe Middle East, and Africa

Europe Tel: +31 (0) 40 29 01 600 eupresales@handheld.com United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com France
Tel: +33 (0) 1 41 158220
eupresales@ handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@ handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@ handheld.com

Offices Serving Asia and the Pacific Rim Hong Kong Tel: +852 2511 3050 appresales @ handheld.com Japan Tel: +813 5770 6312 appresales@handheld.com

Shanghai Tel: +86 21 6361 3818 appresales@handheld.com

Offices Serving Latin America Naples, Florida Tel: +1 239 263 7600 lapresales@handheld.com

lapresales @ handheld.com São Paulo
Tel: +55 11 2178 0500
lapresales @ handheld.com Rio De Janeiro
Tel: +55 21 2178 0500
lapresales @ handheld.com Mexico
Tel: +52 55 5203 2100
lapresales @ handheld.com

Web Site Address www.handheld.com web Site Address www.nanneto.com
Hand Held Products, Inc., ("Hand Held Products")
1999-2005. All rights reserved. Printed in the U.S.A.
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.