

STYLISH AND INNOVATIVE 4 INCH RECEIPT/LABEL PORTABLE PRINTER

LK-P41

- High gloss cover and 3 color LEDs
- Adjustable paper width from 25.4mm to 112mm
- 2 types of battery selectable - 2200/4400mAh Li-ion
- Large capacity, paper rolls up to 56mm(OD)
- Highly reliable Bluetooth communications or Wi-Fi(802.11b/g) available(OPTION)
- ESC/POS, CPCL command compatible
- Various O/S drivers : Win CE/Mobile, Symbian, Linux, Blackberry



● SPECIFICATION

| | | |
|--------------------------|---|--------------------------------|
| PRINT METHOD | | Direct Thermal |
| PRINTING SPEED | | 80mm/sec |
| DOT DENSITY | | 203DPI |
| DOT PITCH | | 8 dots/mm, 0.125pitch |
| EFFECTIVE PRINTING WIDTH | | 104mm, 832dots/line |
| PAPER | TYPE | Thermal paper / Label |
| | WIDTH | 25.4mm ~ 112mm |
| | THICKNESS | 0.06mm ~ 0.16mm |
| | ROLL DIAMETER | Max. Ø 56.0mm |
| | ROLL CORE INNER DIAMETER | 12.5mm ± 0.5mm |
| RELIABILITY | TPH LIFE | 50km |
| | PULSE ACTIVATION | 50,000,000pulse or more |
| FONTS and GRAPHICS | STANDATD FONTS | Seven resident fonts 12-48 pt. |
| | OPTIONAL | International character sets |
| | GRAPHICS, LINE AND BOX DRAWING | PCX and Bitmap |
| BARCODE | EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D) | |

| | | |
|-----------------|--|-------------------------------------|
| EMULATION | ESC/POS, CPCL Command compatible | |
| DRIVER | Window Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows(CE 4.2 & 5.0 / Mobile 5.0), Linux Printer Driver, Symbian, Blackberry | |
| SENSOR | Paper end / Black mark / Gap / Cover open sensors | |
| INTERFACE | STANDARD | Serial(RS-232C), USB |
| | OPTION | Bluetooth class 2, Wi-Fi(802.11b/g) |
| BATTERY CHARGER | External Charger(Output 8.4VDC / 0.8A) | |
| BATTERY | 7.4V 2200mAh, 3.7Hrs charging time, 20Hrs stand-by | |
| DIMENSION | WxDxH(mm) | 149.2 x 162 x 70 |
| | W"xD"xH"(inch) | 5.87 x 6.37 x 2.75 |
| WEIGHT | 572g (with 2200mAh Battery) | |
| TEMPERATURE | OPERATION | -10 ~ 50°C |
| | STORAGE | -20 ~ 60°C |
| HUMIDITY | OPERATION | 35 ~ 80% |
| | STORAGE | 10 ~ 90% |

● APPLICATION

