

PM66

MULTI-PURPOSE ENTERPRISE RUGGED MOBILE COMPUTER

Powerful Qualcomm Snapdragon will empower your work

Qualcomm's Snapdragon MSM8916 processor is a market-proven AP(Application Processor) which has Quad-Core with up to 1.2GHz clock speed. It is truly SoC(System on a Chip) having 4G LTE, Wireless LAN, Bluetooth, S-GPS and Camera bus interface.

Google Android 6.0.1 Marshmallow is the heart of system

PM66 runs on Google's latest Android 6.0.1 Marshmallow Operating System and it is certified by Google Mobile Services (GMS) to support all Google official API including Google Play and Google Maps.

Wider & Brighter IPS display provides better visibility

PM66 adopts 4.3" IPS panel TFT-LCD with capacitive touch screen and it supports wide-viewing angle and daylight readability in order to maximize the best performance in the out-field. To support harsh environment, top of screen is protected Corning Gorilla Glass 3 tempered glass.

Physical Numeric keys with keypad back-light towards field-work-forces

More and more field-workers requires smartphone-like features in the field, but still fast & accurate input is very critical in terms of productivity, users prefer physical keys instead of touch-based virtual keypad on the screen. Along with keypad at the bottom of 4.3inch screen, PM66 is still light, slim, relatively small form factor against conventional 'brick-style' mobile computers. Each key is wide and big enough for users to input data firmly, fast and accurately. LED back-lit keypad powers ease to work at night and dimmed-light area anywhere.



Powerful Wireless; 4G LTE & IEEE 802.11 a/b/g/n/d/h/i/r and Bluetooth 4.1 LE

As of Enterprise mobility purposes, PM66 is completely tuned for Enterprise work-forces; smooth hand-over between WWAN and WLAN each other, seamless roaming among many routers & access points in the harsh working environment, because Enterprise users prior seamless connectivity to speed. PM66's 4G LTE category 4 is truly designed for covering all worldwide including United States and Europe. Newest Bluetooth Low Energy supports dramatic low power consumption and 3x faster speed than previous Bluetooth version, which specification is getting more critical at location-based solutions like Beacon.

Fully-rugged and versatile for outfield & warehouse/logistic applications

PM66 is slim and light design but still fully-rugged design with IP67 water/dust proof and 1.5meter multi-drop resistant on concrete. PM66 has various configurations, such as full 4G/LTE version for outfield and, at the same time, Wi-Fi-only version for warehouse/logistic applications. For Wi-Fi-only models can be docked with a gun-shaped scan-trigger handle, therefore, it is optimized for scan-intensive applications in warehouses.





































PM66

PHYSICAL CHARACTERISTICS

Dimensions

With standard batt. 166.01mm L x 76.83mm W x 29.27mm D

6.53 in. L x 3.02 in. W x 1.15 in D

Weight

With standard batt. 300g / 10.58oz

Display 4.3", IPS panel (480 x 800 pixel) WVGA

Exceptionally bright

Daylight readable (500 nits typical)

Touch Panel Multi-touch capacitive Corning Gorilla glass

Wet touch Glove touch

3.85V, 4.100mAh Li-ion rechargeable Power

UN38.3 certificate, UL2054/UL1642,

IEC62133 KC/PSE

Supports micro USB charging

Numeric keypad (24 Keys) with backlight Keypad

Audio Support Support VoIP

Two built-in microphones (Noise-cancelling)

Speaker

Receiver and headset jack (3.5mm)

Wireless Bluetooth headset support

Standard Communications and Micro-USB port

High speed USB 2.0 from cradle

Notification

Front 2 x dual color LEDs for Power indication,

Warning indication & Scan reading

Vibration, beep Scan Alert

PERFORMANCE CHARACTERISTICS

Main-Processor

Qualcomm MSM8916 @ 1.2GHz Quad-core

Operating System

Google Android 6.0.1 Marshmallow

(CTS & GMS certified) FOTA (Firmware Over The Air) update is

available via MS Azure™ Cloud

Memory and Storage

RAM ROM (NAND Flash) 16GB

Micro-SD

Micro-SD card slot supports

up to 32GB SDHC

Sensor Proximity sensor

Light ambient sensor Acceleration sensor Gyro and Digital compass

USER ENVIRONMENT

Operating Temperature

-20°C to 60°C / -4°F to 140°F

Storage

-25°C to 70°C / -13°F to 158°F

Temperature

Humidity

95% Non-condensing

Drop

Multiple 1.5m(5 ft) drops to steel over the operating temperature

Water / Dust Proof IP67 (Sealing)

Tumble 500 cycles (1.000 hits) at 1 m / 3.3ft

per IÉC 60068-2-32

Electrostatic Discharge

±15 kV air discharge ±8 kV contact discharge

DATA CAPTURE

Camera

Rear 13MP AF with LED flash

Integrated Barcode Reader

1D Laser Scanner All 1D standard symbology & postal code 2D Imager Scanner All 1D/2D standard symbology

including GS1 databar

NFC (Near Field Communcation)

ISO14443A, ISO14443B & ISO15693 are supportive, 13,56MHz HF *Supported TAG-ICs:

MIFARE® 1k, MIFARE 4k, MIFARE Plus, MIFARE UltraLight, MIFARE UltraLight C, MIFARE DESFire, MIFARE DESFire EV1

ISO 14443A/B tags

GLOBAL POSITIONING SYSTEM

GPS

Integrated GPS, GLONASS and BeiDou.

Simultaneous-GNSS and Standalone-GNSS without WAN

WIRELESS

Wireless WAN

EDGE/GPRS/GSM 900/1800 3G HSPA B1/2/5/6/8/19

LTE (B1,2,3,5,7,8,17,20,40,41) 4G 3G UMTS/HSDPA/HSUPA/HSPA/ HSPA+(B1/2/5/6/8/19)

2G GSM/GPRS/FDGF (900/1800 MHz)

Wireless LAN

IEEE 802.11a/b/g/n/d/h/i/k/r/v, IPv4, IPv6, 1X1 SISO Radio

Data Rates IEEE 802.11a/n: Up to 150 Mbps; IEEE 802.11b/g/n: Up to 72.2 Mbps

Operating 1 to 13 (2412~2472MHz). 36 to 165 (5180~5825MHz) Channels

20 40 80MHz Channel

Regulatory Compliance As per IEEE 802.11n

WEP(40 or 104bit) WPA/WPA2 Personal(TKIP, AES); Security and Encryption

WPA/WPA2 Enterprise(TKIP/AES) PEAP(MSCHAPv2, GTC), TLS, TTLS(PAP, MSCHAP, MSCHAPv2, GTC), PWD, SIM, AKA, AKA', FAST(MSCHAPv2, GTC), LEAP

Fast Roam PMKID Caching: Cisco CCKM, 802.11r

Wireless PAN

REGULATORY APPROVALS AND COMPLIANCE

Certified CE, CB, CEC, CU, FAC, FCC, IC, PTCRB, KC, RCM, WPC, BIS Environmental: RoHS II, WEEE compliant

ENTERPRISE SOLUTION

SOTI, Airwatch, Teamviewei



Power Launcher

Kiosk mode with system restriction Allows admin to restrict operator's access to system settings, MTP connection and screen capture

Direct Clone Master PDA becomes a local server for

a nearby Point Mobile device to automatically communicate and download/restore backup files

Unique two-step feature for Point Scan2Set

> Mobile Android models that enables the fastest device deployment right out of

ACCESSORIES

Standard Accessories



Standard Battery



LCD Protection Film

Optional Accessories

4-Slot Battery Charger



Single-Slot Cradle



4-Slot Cradle

Gun-Handle



Integrated Bluetooth Class I, Ver. 4.1

