

3820Retail/Commercial Cordless Scanning System



Adaptus TM Imagin

Adaptus™ Imaging Technology - Hand Held Products exclusive brand of imaging technology provides best-inclass read range and an unsurpassed ability to read poor quality bar codes. Both features are well suited to cordless applications where improved efficiency and ergonomics are primary goals.

Bluetooth® v1.2 Class 2 Radio - Developed to reduce interference in existing RF backbones, including 802.11. Only v1.2 uses Adaptive Frequency Hopping (AFH) to mitigate data collisions in the 2.4 GHz frequency band, while providing a 33 foot (10m) working range.

Unique Base Design offers the following features:

- A minimal footprint that is up to 33% smaller than major competitors', simplifying installation and leaving more counter space for customer service or other application needs.
- Presentation scanning with a docked imager for efficient, hands-free bar code reading.
- Host-powered interface and RF link; an exclusive Hand Held Products feature that extends the mobile capabilities of the 3820 by drawing power from a portable device for radio and host communications.

Battery - A long lasting, high capacity lithium ion battery provides 57,000 scans per full charge with no conditioning required. The battery is field-replaceable.

Durable - Hand Held Products solid state, no-moving-parts imager design withstands more than fifty 6 foot (1.8m) drops to concrete.

2005 Sunrise Compliant!

Hand Held Products 3820 combines exclusive Adaptus Imaging Technology with Bluetooth wireless connectivity to provide class-leading performance and durability for retail and commercial cordless bar code reading.

In applications where operators must move about to read bar codes, cables become a limiting factor. They cause inefficiencies or safety and ergonomic concerns. Cable length often limits working range, resulting in an object being moved to the reader because the reader can't be taken to the object. With cordless bar code reading, operators have freedom of movement required to quickly, safely, and ergonomically read bar code data. With a 33 foot (10m) working range and 24 inch (61cm) read-range, the 3820 has the right combination of performance and features.

Having the right performance is only part of the solution; staying in service is just as important. The 3820 also has class-leading durability. It was designed to survive in real world mobile applications. Hand Held Products is committed to creating some of the most rugged products available, and the 3820 is another example of that commitment. With no moving parts and a robust housing design, the 3820 will easily provide years of service in retail and commercial environments, creating a favorable total cost of ownership.

For information on how the 3820 can make your business more efficient, contact us at any of the locations listed on the back or visit us at www.handheld.com.

3820 Specifications

Performance

Illumination: 630 NM Visible Red LED 3648 element linear imager **Receiving Device:**

Reading Distance: From 1 in. (2.5 cm) to 24 in. (61 cm) on medium density codes Reading Width: 7.5 mil code: 7 in. (18 cm) from nose, 6.6 in. (17 cm) wide 13 mil code: 16.5 in. (42 cm) from nose, 10 in. (25 cm) wide

Resolution: 5 mil. at 5 in. (13 cm) distance

Skew Angle: +65° <u>+</u>65° Pitch Angle: **Minimum Symbol Contrast:** 20%

Scan Rate: Up to 270 scans per second Decode Rate: 270 decodes per second

Mechanical/Electrical

3820 Scanner with Battery 2020 Base **Dimensions** 9.2 oz. (261 g) 8.8 oz. (250 g) w/o cable Weight: Height: 6.5 in. (16.5 cm) 3.1 in. (7.9 cm)

Power Requirements

4.5 to 12 VDC (host) Input Voltage: 3.6 V internal battery 8.5 to 9.5 VDC brick

Current Draw Operating: N/A Standby: N/A

125 mA max @ 5V (no charging) 100 mA max @ 12V (no charging) 825 mA max @ 12V (charging)

Environmental

Sealing: IP 41 (Water and Dust Resistant) IP 41 (Water and Dust Resistant)

Temperature 32° to 122°F (0° to 50°C) Operating: Storage: -40° to 140°F (-40° to 60°C)

-40° to 140°F (-40° to 60°C) **Humidity:** up to 95%, non condensing up to 95%, non condensing **Mechanical Shock:** Functional after 50 drops from 6 ft. (1.8 m) Functional after 50 drops from 3.3 ft. (1 m)

Ambient Illumination: 0-76,000 lux

ESD Protection: Functional after 15 kV discharge

Radio

2.4 to 2.4835 GHz (ISM Band) Frequency-Hopping Bluetooth v. 1.2 Frequency:

Range: 33 ft. (10 m) typical

Data Rates: 720 KBps **Battery** Lithium Ion Capacity: 2.000 mAh **Number of Scans:** 57,000

Expected Hours of Operation: 16 hours @ 1 scan every second Charge Time with 9 VDC brick:

Symbologies:

4 hours for full charge from full discharge

China Post, Codabar, Codablock F, Code 2 of 5, Code 11, Code 16K, Code 39, Code 32 Pharmaceutical (PARAF), Code 49, Code 128, EAN/JAN, IATA Code 2 of 5, Interleaved 2 of 5, Korea Post, Matrix 2 of 5, Coupon Code, MSI, Plessey Code, PosiCode, RSS-14, Telepen, Trioptic, UPC-A, and UPC-E. 2005 Sunrise/GTIN compliant.

All popular PCs and terminals via keyboard wedge, keyboard Interfaces:

replacement/direct connect, USB, TTL level RS-232, wand emulation mode, TTL level Serial Wedge, and IBM 46XX retail terminals.

BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed to Hand Held Products.

Bluetooth

32° to 122°F (0° to 50°C)

Worldwide Offices

Offices Serving North America Skaneateles Falls, NY Tel: +1 315 685 8945

or, in North America: +1 800 582 4263 napresales@handheld.com Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@ handheld.com

Offices Serving Europe Middle East, and Africa

Europe Tel: +31 (0) 40 29 01 600 eupresales@handheld.com United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com France
Tel: +33 (0) 1 41 158220
eupresales@ handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@ handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@ handheld.com

Offices Serving Asia and the Pacific Rim Hong Kong Tel: +852 2511 3050 appresales @ handheld.com Japan Tel: +813 5770 6312 appresales@handheld.com Shanghai Tel: +86 21 6361 3818 appresales@handheld.com

Offices Serving Latin America Naples, Florida Tel: +1 239 263 7600 lapresales@handheld.com lapresales @ handheld.com São Paulo
Tel: +55 11 2178 0500
lapresales @ handheld.com Rio De Janeiro
Tel: +55 21 2178 0500
lapresales @ handheld.com Mexico
Tel: +52 55 5203 2100
lapresales @ handheld.com

Web Site Address www.handheld.com web Site Address www.nanneto.com
Hand Held Products, Inc., ("Hand Held Products")
1999-2006. All rights reserved. Printed in the U.S.A.
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.