



# *IMAGETEAM<sup>™</sup> 4710HD/HD10* Fixed Mount 2D Image Reader

The Hand Held Products IMAGETEAM<sup>™</sup> (IT) 4710 Image Reader can be configured as either a hand held or fixed mount device that reads matrix, stacked linear and conventional linear bar codes, as well as a single line of OCR-A and OCR-B fonts. Multi-line OCR applications can also be read. The IT4710 has the power to capture and download images to a PC for applications that include signature capture, PCbased decoding, and image lift requirements.

The IT4710 Reader can be used in retail, transportation, packaging, printed circuit board manufacturing, electronic component manufacturing, and clinical/diagnostic applications that include test tube and reagent package labels.

The IT4710 can be configured for keyboard wedge, HHLC (Code 128 emulation), TTL, or True RS-232. The IT4710 connects to all popular PCs and portable data terminals. HHLC mode can be used with external wedge decoders and portable terminals or other devices without 2D decoding capability.

The IT4710 features integrated processing for a one-piece scanning solution -- no additional boxes or electronics needed. The reader provides omni-directional and auto-discrimination decoding for symbologies, such as MaxiCode, PDF417, QR, Data Matrix, Aztec code, RSS code, composite codes, postal codes, Code 39, Code 93, Interleaved 2 of 5, Codabar, Code 128, UPC, and EAN. Additional symbologies will be added based on market demand.

Because the IT4710 is a fixed focus device, four product models with different focal points are available. Two high density scanners are available: IT4710HD and IT4710HD10. The IT4710HD, with a focal point of 2 inches, is recommended when the matrix symbols are less than 10 mil. The IT4710HD10 is recommended for applications when the matrix codes are greater than 10 mil. This version, with a focal point of 3 inches, maximizes the depth of field on 10 mil matrix codes, which directly correlates to greater functionality by the end user. The long range (LR/LX) models of the IT4710 are highlighted in separate data sheets.

### Features & Benefits

#### 2D Image Reader

Hand held or fixed mount image reader for reading and decoding 2D symbologies, and capturing images.

#### Supports All Popular 2D Symbologies

Fixed mount IT4710 supports all popular matrix and stacked linear symbologies: MaxiCode, Aztec, Aztec Mesa, Data Matrix, PDF417, QR, and MicroPDF417.

#### Fixed Position Reader

Opens up new 2D bar code and image capture possibilities for fixed scanning applications.

#### **Omni-Directional Scanning**

The video technology offers omni-directional scanning, even on linear codes, greatly simplifying operator training and increasing productivity.

#### Aiming

The IT4710 has a bright, intuitive aiming line.

### Autodiscriminates Between Supported Symbologies and Fonts

Reads all major linear, stacked linear, and matrix bar codes as well as machine readable fonts used in Optical Character Recognition (OCR).

<u>IMAGETEAM</u>	<u>/////////////////////////////////////</u>	ID10			
Performance					
HD Focal Point: HD10 Focal Point:	2 inches from nose 3 inches from nose				
HD Working Range: (typical) Near Far	6 pt OCR <u>20 cpi</u> 2 in. (5.1 cm) 3.5 in. (8.9 cm)	<b>6.6 mil QR</b> (.017 cm) 1.7 in. (4.3 cm) 2.45 in. (6.2 cm)	6.6 mil Data Matrix (.017 cm) 1.7 in. (4.3 cm) 2.45 in. (6.2 cm)	<b>4 mil Linear</b> ( <u>.01 cm)</u> 1.6 in. (4.6 cm) 2.7 in. (6.9 cm)	
HD10 Working Range: (typical)	10 mil QR <u>(.025 cm)</u>	10 mil Data Matrix <u>(.025 cm)</u>	5 mil Linear <u>(.013 cm)</u>		
Near Far	2.0 in. (5.1 cm) 4.0 in. (10.2 cm)	2.2 in. (5.6 cm) 3.8 in. (9.6 cm)	2.75 in. (7.0 cm) 3.75 in. (9.5 cm)		
<b>Rotational Sensitivity:</b>	360°				
Viewing Angle:	<u>+</u> 45°				
Ambient Light:	Total darkness to 100,000 lux (full sunlight)				
Aiming:	660nm LEDs provide bright aiming line				
Symbologies 2 Dimensional:	MaxiCode, PDF417, MicroPDF417, Aztec, Aztec Mesa, Data Matrix, QR Code, Code 49, UCC Composite, Snowflake*, Vericode*, Dataglyphs*				
Linear:	Code 39, Code 128, Codabar, UPC, EAN, I 2 of 5, RSS, BC 412*, Code 93, Codablock * available to licensed users only				
Postal:	Postnet (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code				

OCR Fonts:	OCR-A, OCR-B
Interfaces:	RS232, Wedge, and HHLC (Code 128 Emulation)
Programable Options:	Baud, Parity, Data Formatting, Code Options

#### Mechanical/Electrical

Dimensions	
Length:	4.85 in. (12.3 cm)
Height	1.85 in. (4.7 cm)
Width:	2.50 in. (6.35 cm)
Weight w/o cord:	5.5 oz. (156 g) or less
<b>Power Requirements:</b>	4 to 9 volts
Current Draw:	Low Power Mode - average @ 5 VDC-40mA Medium Power Mode - average @ 5 VDC-125mA High Power Mode - average @ 5 VDC-175mA
Standby Current:	< 200µA @ 5V

#### Environmental


Temperature Operating:	-0°C to 50°C
Storage:	-40°C to +70°C
Humidity:	95% RH, non condensing at 50°C
Shock:	10 drops 5 ft. to concrete @ room temperature
ESD:	Functional after 15KV discharge
Agency:	FCC Class B, CE

Europe

France

## CE

*Germany* Tel: Int +49 (0) 7 477 151377 Fax: Int +49 (0) 7 477 151378 Offices Serving Asia and the Pacific Rim Hong Kong Tel: Int +852 2511 3050/2511 3132 Fax: Int +852 2511 3557 Japan Tel: Int +813 52127392 Fax: Int +813 32617372



Offices Serving Latin America Naples, Florida Tel: (941) 263-7600 Fax: (941) 263-9689

Web Site Address www.handheld.com

Welch Allyn Data Collection, Inc. and Hand Held Products, Inc. ("Hand Held Products") <sup>©</sup> 1999-2001, Hand Held Products. All rights reserved. Printed in the U.S.A. Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.

Offices Serving Europe, Middle East, and Africa

Tel: Int +31 (0) 40 24 24 486 Fax: Int +31 (0) 40 24 25 672

United Kingdom Tel: Int +44 (0) 1 925 240055 Fax: Int +44 (0) 1 925 631280

Tel: Int +33 (0) 1 461 04111 Fax: Int +33 (0) 1 461 04120

Worldwide Offices

Tel: (315) 685-8945 or, in the U.S.: (800) 782-4263 Fax: (315) 685-3172

Skaneateles Falls, NY

Charlotte, NC

Tel: (704) 537-1444 Fax: (704) 532-4191

**Offices Serving North America**