

NLS-EM20-80

OEM Scan Engine



Features

■ Snappy On-screen Barcode Capture

Featuring excellent near-field reading, wide-viewing angle and snappy reading, the CPU-powered NLS-EM20-80 is incredibly reader-friendly on smartphone & tablet displays.

■ Robust Design with High Vibration Resistance

The single PCB construction and vibration-proof connectors make the scan engine more resistant against vibration and help improve its reliability.


■ Multiple Interfaces

The NLS-EM20-80 supports USB, RS-232 and

■ Slimmer, More Compact Construction

Compared with its predecessor, the new generation of NLS-EM20 is thinner, lighter and more compact, and thus easier to be integrated into any devices.

■ Outstanding Power Efficiency

The advanced  technology incorporated in the scan engine helps reduce its power consumption and prolong its service life.

Application Scenarios (as an accessory)

Bus POS terminals, VTMs, self-service cabinets used in e-commerce, express delivery services and smart homes, kiosks, automatic queuing machines, vending machines, etc.

NLS-EM20-80

OEM Scan Engine

SCANNING MADE SIMPLE

Performance	Image Sensor	640 * 480 CMOS			
	Illumination	White LED			
	Symbologies	2D	PDF 417, QR Code, Micro QR, Data Matrix, Aztec, Maxicode, Chinese Sensible Code, GM Code, Micro PDF417 Code, Code One		
		1D	EAN-8, EAN-13, UPC-E, UPC-A, Code 128, UCC/EAN128, I2Of5, ITF-14, ITF-6, Matrix 25, CodaBar, Code 39, Code 93, ISSN, ISBN, Industrial 25, Standard 25, Plessey, Code11, MSI-Plessey, UCC/EAN Composite, GS1 Databar, Code 49, Code 16K		
	Resolution*	≥5mil			
	Typical Depth of Field*	EAN-13	25mm-110mm (13mil)	PDF417	35mm-45mm (6.7mil)
		QR Code	0mm-90mm (15mil)	Data Matrix	35mm-50mm (10mil)
		Transport Code:	38mm-135mm		
	Min. Symbol Contrast*	30%			
	Scan Angle**	Roll: 360°, Pitch: ±40°, Skew: ±45°			
	Motion Tolerance*	Hangzhou Transport Code:	110cm/s (max)		
		Wechat Pay:	260cm/s (max)		
	Field of View	Horizontal 68°, Vertical 51°, Diagonal 84.8°			
Mechanical/ Electrical	Interface	TTL-232, RS-232, USB			
	Operating Voltage	12-pin FPC connector: 3.3-5VDC±5% 4-pin box connector: 3.3-5VDC±5%			
Rated Power Consumption@5VDC	1129mW (typical)				
Current@5VDC	Operating	237mA (typical), 319mA (max.)			
	Idle	69mA			
Rated Power Consumption@3.3VDC	1103mW (typical)				
Current@3.3VDC	Operating	335mA (typical), 479mA (max.)			
	Idle	93mA			
Dimensions	61.5(W)×65.5(D)×31.9(H)mm (max.)				
Weight	33g				
Notification	Beeper, Green LED Indicator				
Environmental	Operating Temperature	-40°C to 60°C			
	Storage Temperature	-40°C to 75°C			
	Humidity	5% to 95% (non-condensing)			
	Ambient Light	0~100,000lux (natural light)			
Certifications	FCC Part15 Class B, CE EMC Class B				
Accessories	NLS-EVK	Software development board for the NLS-EM20-80, equipped with a trigger button, beeper and RS-232 & USB interfaces.			
	Cable	USB	Used to connect the NLS-EVK to a host device.		
		RS-232	Used to connect the NLS-EVK to a host device.		
	Power Adapter	DC5V power adapter to power the NLS-EVK with RS-232 cable.			

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland, WeChat Pay QR code on a 5.5" Android smartphone with brightness set to 100%.

**Test conditions: Scan Distance=(min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;
2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version: V1.1

Newland China

+86-591-83978605
contact@nlsan.com
www.newlandaidc.com

Newland Europe

+31(0)-345-87-0033
info@newland-id.com
www.newland-id.com

Newland North America

+1-510-490-3888
info@newlandna.com
www.newlandamerica.com

Newland Latin America

+1-239-598-0068
info@newlandla.com
www.newlandamerica.com

Newland Taiwan

+886-2-7731-5388
info@newland-id.com.tw
www.newland-id.com.tw

Newland Korea

+82-10-8990-4838
th.sung@newland-id.com.tw
www.newlandaidc.com

