



IR-2000/-HD



- **IMAGETEAM™ 4410ESD**
- **IMAGETEAM™ 4410HD**
- **IMAGETEAM™ 4410LR/LX**
- **IMAGETEAM™ 4710 Fixed Mount**

추천모델



THIR-3000



ICLS-2002
(신제품)

Lesetechnik/Lichtquelle:	CCD Area
Auflösung, minimal:	10 mil/5 mil (HD)
Scanmuster:	360°
Scantiefe/Sichtfeld:	4,3 x 3,0 cm / 7,6 cm 12,7 x 8,9 cm / 21,6 cm 17,8 x 12,7 cm / 30,5 cm 2,4 x 1,8 cm / 8,9 cm (HD)
Schnittstelle:	RS-232
Datenformat:	ASCII oder Bitmap
Übertragungsrate:	600 - 115.200 BPS
Triggering:	Taster
Lesbare Codes 2D:	Data Matrix Code, Maxicode, PDF417, QR Code
1D:	UPC, EAN, Code 39, Code 128, Codabar, Interleaved 2/5
Konfiguration:	über Handbuch
Zulassungen:	CE
Gewicht:	138g

Features

- Intuitive Aiming
- Integrated 2D Digital Imager
- Ergonomic Design
- Omni-Directional Scanning
- Autodiscriminates among Symbologies and Fonts

Benefits

- Present bar codes from any angle for increased throughput and ease of use.
- Finds bar codes and frames images quickly for increased productivity.
- Supports all major linear, stacked linear (PDF417), and matrix bar code symbologies, OCR fonts, and image capture.
- Accommodates left/right hand users. Non-skid rubber stabilizes mounting points for secure attachment to counter stand
- No action is required to differentiate OCR fonts from standard bar code. Labels are automatically read as they are presented.

- Length: 157mm
- Width: 57mm
- Depth: 68mm
- Weight: 175g

- Pitch: ±35 °
- Skew: ±35 °
- Rotation: 360 °
- Ambient Light: 50Lux to 10000Lux

- 50mm 36X 27mm
- 100mm 64X 48mm
- 150mm 92X 69mm
- 200mm 119X 89mm

- 1차원 바코드 : Code 39, Code128외
- 2차원 바코드 : PDF-417, DataMatrix, QR, MaxiCode

- RS-232, USB
- Format : ASCII or Bitmap